



ZI Series



Technical Specifications

Technical Specifications(R410A-DC Inverter)						
Model No.			TAC-09CHSA/ZI	TAC-12CHSA/ZI	TAC-18CHSA/ZI	TAC-24CHSA/ZI
Type			heating pump	heating pump	heating pump	heating pump
Rated cooling capacity	Btu/h		9,000	12,000	18,000	24000
	W		2,640	3,520	5,280	7030
Rated heating capacity	Btu/h		10,250	13,800	20,000	24500
	W		3,000	4,050	5,860	7180
EER for cooling	Btu/h. w; W/W		11.54; 3.39	11.32; 3.32	11.04; 3.24	10.95; 3.21
COP for heating	W/W		3.66	3.62	3.2	3.21
Moisture removal	Liters/h		0.8	1	2	2.5
Power supply		220-240V~/50Hz/1P				
Refrigerant/Charge	Gram		R410A / 680g	R410A / 880g	R410A / 1500g	R410A / 2400g
Suitable area		m ²	9-16	15-23	25-40	30-50
Net dimensions (W x H x D)	Indoor	mm	770x240x180	770x240x180	900x280x202	1033x313x202
	Outdoor	mm	760x552x256	760x552x256	820x605x300	900x805x360
Net weight	Indoor	kg	8	8	11	14
	Outdoor	kg	30	32	40	61
Packing dimensions (W x H x D)	Indoor	mm	855x305x255	855x305x255	995x365x298	1103x400x300
	Outdoor	mm	863x598x376	863x598x376	965x650x438	1031x925x447
Gross weight	Indoor	kg	10	10	14	17
	Outdoor	kg	33	36	44	66

Features

-  Auto-protection
-  Chord Response
-  Strong Cooling
-  10-hour Auto Power Off
-  Auto Restart
-  Ioniser
-  Timer Mode
-  Global Power Supply Design(Plug)
-  6 Layers Rust Free
-  Independent Dehumidification
-  Anti-mildew
-  Soft-starter Kit
-  Anti-cold Air
-  High Efficient Internal Thread Copper Pipe
-  Easy-clean Panel & Filters
-  Sleep Mode
-  Quiet Operation
-  Intelligent Defrost